

Developer Guide

Contains all the information relating to using the VirtualPlayers API.

- [Getting Started](#)
- [VirtualPlayers API](#)

Getting Started

VirtualPlayers comes with an API which can be used by developers. Follow the steps below to add the API as a dependency.

Adding the BattlePlugins Repository

Gradle (Kotlin DSL)

```
repositories {  
    maven("https://repo.battleplugins.org/releases")  
    maven("https://repo.battleplugins.org/snapshots")  
}
```

Gradle (Groovy)

```
repositories {  
    maven {  
        url "https://repo.battleplugins.org/releases"  
    }  
    maven {  
        url "https://repo.battleplugins.org/snapshots"  
    }  
}
```

Maven

```
<repositories>  
    <repository>  
        <id>battleplugins-releases</id>  
        <name>BattlePlugins Releases</name>  
        <url>https://repo.battleplugins.org/releases</url>  
    </repository>  
    <repository>  
        <id>battleplugins-snapshots</id>  
        <name>BattlePlugins Snapshots</name>
```

```
<url>https://repo.battleplugins.org/snapshots</url>
</repository>
</repositories>
```

Adding the Dependency

Gradle (Kotlin DSL)

```
dependencies {
    compileOnly("org.battleplugins.virtualplayers:api:3.0.0")
}
```

Gradle (Groovy)

```
dependencies {
    compileOnly "org.battleplugins.virtualplayers:api:3.0.0"
}
```

Maven

```
<dependencies>
    <dependency>
        <groupId>org.battleplugins.virtualplayers</groupId>
        <artifactId>api</artifactId>
        <version>3.0.0</version>
        <scope>provided</scope>
    </dependency>
</dependencies>
```

VirtualPlayers API

The VirtualPlayers API can be accessed through the [**VirtualPlayers**](#) class, by calling **VirtualPlayers.api()**.

A [**VirtualPlayer**](#) can be created using the **createVirtualPlayer(String)** method. A [**VirtualPlayer**](#) extends Bukkit's **Player** class, meaning all functions available to a normal **Player** will be available here. Keep in mind that some methods may not work as intended, since a [**VirtualPlayer**](#) is.. well... a virtual player at the end of the day, so functionality like sending block changes or adding them as a passenger to an entity will not work.

Within the [**VirtualPlayer**](#) class, you can also run **addObserver(CommandSender)** to observe a virtual player. You can also get a list of all observers by running **getObservers()**.

VirtualPlayers can be removed using the **removeVirtualPlayer(VirtualPlayer)** method in the [**VirtualPlayers**](#) API class. You can also retrieve a [**VirtualPlayer**](#) by calling **getVirtualPlayer(String)**, taking in the name of the [**VirtualPlayer**](#).

For a full list of methods and classes offered by the API, see the VirtualPlayers [**Javadocs**](#).